ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM O.M.B. No. 3067-0077 Expires July 31, 1999

ATTENTION: Use of this certificate vide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages.

	SECTION A P	TION A PROPERTY INFORMATION			FOR INSURANCE COMPANY USE	
BUILDING OWNER'S NAME Bednash, Chri	stine				POLICY NUMBER	
STREET ADDRESS (Including A) 109 Clearwate OTHER DESCRIPTION (Lot and	r Drive		ROUTE AND BOX NUMBER		COMPANY NAIC NUMBER	
	ean TwpOc	ean Co.)	New J	ersey	0.8.7.5.8	
				STATE	ZIP CODE	
			NCE RATE MAP (FIRM)	INFORMATION		
Provide the following from t	he proper FIRM (Se	FIRM (See Instructions):				
1. COMMUNITY NUMBER 340518	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX 1 / 06 / 83	5. FIRM ZONE A 5	6. BASE FLOOD ELEVATION (in AO Zones, use depth)	
8. For Zones A or V, where	no BFE is provided	m used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) provided on the FIRM, and the community has established a BFE for this building site, indicate feet NGVD (or other FIRM datum—see Section B, Item 7).				
-	SECT	ION C BUILDII	NG ELEVATION INFORM	MOITA		
 (c). FIRM Zone A (without below (check one) (d). FIRM Zone AO. The flone) the highest grade level) elevated in accordance. 3. Indicate the elevation dat under Comments on Page the FIRM [see Section Enguation under Comments] 4. Elevation reference mark 	alding's reference le AE, AH, and A (with the NGVD (or other FlovE, and V (with BFE) is at an elevation of BFE). The floor use the highest grade a loor used as the reference with the commun system used in the elevation (NOTE: If the elevation of the public of the public of the public of the public of the elevation of the elevat	BFE). The top of RM datum—see (a). The bottom of the botto	of the reference level floo Section B, Item 7). If the lowest horizontal str feet NGVD (or other FIR nee level from the selected uilding. In the selected diagram is depth number is available ain management ordinance above reference level ele- in used in measuring the ele- ter to the datum system used.	r from the selecter uctural member of M datum—see Sed diagram is feet above, is the building's ee? Yes NGVI levations: X NGVI levations is different and Page 4)	d diagram is at an elevation of the reference level from ction B, Item 7). J. L feet above or ove or below (check s lowest floor (reference) No Unknown D'29 Other (describe)	
5. The reference level eleva (NOTE: Use of construct case this certificate will on will be required once cons	tion is based on: in the state of the state	actual construction valid if the build if the build if the build illding during the	ction construction drawn does not yet have the	awings	oor in place, in which ' on Elevation Certificate	
6. The elevation of the lowes Section B, Item 7).	st grade immediately	nmediately adjacent to the building is: 4 .0 feet NGVD (or other FIRM datum-see				
	S	ECTION D CO	MMUNITY INFORMATIO	N		
If the community official re is not the "lowest floor" as floor" as defined by the on 2. Date of the start of constru	dinance is:	LL feet No	in management ordinanci GVD (or other FIRM datui	e, the elevation of	f the building's "lowest	
FEMA Form 81-31, AUG 96	REPLACES	ALL PREVIOUS EDI	TIONS	SEE REVE	RSE SIDE FOR CONTINUATION	

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

Leon J. Tyszka	# 35888					
CERTIFIER'S NAME	LICENSE NUMBER (or Affix Sea!)					
P.L.S.	Nelke/Tyszka Land Surveyors					
TITLE-	COMPANY NAME					
382 W. 9th Street	, Suite #4, Ship Bottom, New Jersey 08008					
ADDRESS	, Suite #4, Ship Bottom, New Jersey 08008 CITY STATE ZIP					
\propto () 7						
SIGNATURE	August 5, 1997 609-494-3474 DATE PHONE					
	PAUL					
Conjec should be made of this	California (S. 100)					
copies should be made of this	Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.					
COMMENTS:						
ON	WITH ON PILES					
SLAB	WITH ON PILES, BASEMENT PIERS, OF COLUMNS					
A V	A V					
ZONES ZONES	ZONES ZONES TO					
	REFERENCE					
REFERENCE LEVEL MT TM	BASE LEVEL THE REFERENCE					
	FLOOD ELEVATION					
BASE FLOOD	BASE FLOOD					
ELEVATION REFEREN	DE ADJACENT GRADE LEVEL					
LEVEL	GRADE					
	ADJACENT GRADE					
	ATM KANAMA SARAH SANAMA					
The diagrams above illustrate	the points at which the elevations should be measured in A Zones and V Zones.					
The diagrams above mustrate	the points at which the elevations should be measured in A Zones and V Zones.					

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.