U.S. DEPARTMENT OF HOMELAND SECURITY

Federal Emergency Management Agency National Flood Insurance Program

OMB No. 1660-0008 Expiration Date: November 30, 2018

ELEVATION CERTIFICATEImportant: Follow the instructions on pages 1–9.



A1. Building Owne		HON A - PROPERTI	INFORMATION			ANCE COMPANY U
Belfer 2 Properties					Policy Numb	per:
A2. Building Street Box No. 23 Sands Point Roa		cluding Apt., Unit, Suit	e, and/or Bldg. No.)	or P.O. Route and	Company N	AIC Number:
City			State		ZIP Code	
Waretown			New J		08758	
A3. Property Describer 192 Lot 8	ription (Lot a	nd Block Numbers, Ta	ax Parcel Number, L	egal Description, etc.	c.)	
A4. Building Use (e.g., Resider	ntial, Non-Residential,	Addition, Accessory	, etc.) Residentia	ıl	
A5. Latitude/Longit	ude: Lat. <u>3</u>	9°48'28.1"	Long. 74°10'41.7"	Horizontal	Datum: NAD 1	927 🗵 NAD 1983
A6. Attach at least	2 photograp	hs of the building if the	e Certificate is being	g used to obtain flood	d insurance.	
A7. Building Diagra	m Number	6				
A8. For a building	with a crawls	pace or enclosure(s):				
a) Square foot	age of crawl	space or enclosure(s)		861.00 sq ft		
b) Number of p	ermanent flo	ood openings in the cr	awispace or enclos	ure(s) within 1.0 foot	above adjacent gra	de 5
c) Total net are	ea of flood o	penings in A8.b	1000.00 sq	in		
d) Engineered						
A9. For a building w	uith an attack	ned garage:				
		ned garage	210.00 sq	. 4		
a) Square 1000				1 11		
					acest grade 2	
b) Number of p	ermanent flo	ood openings in the at	tached garage withi	n 1.0 foot above adja	acent grade 2	
b) Number of p	ermanent flo		tached garage withi	n 1.0 foot above adja	acent grade 2	
b) Number of p	permanent floea of	ood openings in the at	tached garage withi	n 1.0 foot above adja	acent grade 2	
b) Number of pc) Total net are	permanent floe ea of flood op flood openin	ood openings in the at penings in A9.b gs? ⊠ Yes ☐ N	tached garage withi	n 1.0 foot above adja sq in		
b) Number of p c) Total net are d) Engineered	permanent floe ea of flood op flood openin	ood openings in the at penings in A9.b gs? X Yes N	tached garage withi 400.00	n 1.0 foot above adja sq in E MAP (FIRM) INF		B3. State
b) Number of p c) Total net are d) Engineered	permanent flore of flood opening SE	ood openings in the at penings in A9.b gs? ⊠ Yes ☐ N	tached garage withi	n 1.0 foot above adja sq in E MAP (FIRM) INF		B3. State New Jersey
b) Number of p c) Total net are d) Engineered B1. NFIP Communications	permanent flore of flood opening SE	ood openings in the at penings in A9.b gs? X Yes N	tached garage within 400.00 stacked st	n 1.0 foot above adja sq in E MAP (FIRM) INF	ORMATION B9. Base Flood El	New Jersey
b) Number of p c) Total net are d) Engineered B1. NFIP Community Township of Ocean	permanent floes of flood opening flood opening set of flood opening set	pood openings in the at penings in A9.b gs?	tached garage within 400.00 see the second s	n 1.0 foot above adjassq in E MAP (FIRM) INFoty Name bunty B8. Flood	ORMATION B9. Base Flood El	New Jersey evation(s)
b) Number of p c) Total net are d) Engineered B1. NFIP Community Township of Ocean 4. Map/Panel Number 4029C0416 B10. Indicate the s	permanent flore a of flood opening flood ope	pood openings in the attended openings in A9.b gs?	B7. FIRM Panel Effective/ Revised Date 09-29-2006	n 1.0 foot above adjassq in E MAP (FIRM) INFoty Name bunty B8. Flood Zone(s) AE	ORMATION B9. Base Flood E (Zone AO, use	New Jersey evation(s)
b) Number of p c) Total net are d) Engineered B1. NFIP Communit Township of Ocean 4. Map/Panel Number 4029C0416 B10. Indicate the s	permanent flore a of flood opening flood ope	bod openings in the attended penings in A9.b gs?	B7. FIRM Panel Effective/ Revised Date 09-29-2006 (BFE) data or base mined Other/S	n 1.0 foot above adjaces in E MAP (FIRM) INFO ty Name bunty B8. Flood Zone(s) AE flood depth entered ource:	ORMATION B9. Base Flood E (Zone AO, use	New Jersey evation(s)
b) Number of p c) Total net are d) Engineered B1. NFIP Communit Township of Ocean 4. Map/Panel Number 4029C0416 B10. Indicate the s	ea of flood opening flood open	bood openings in the attended penings in A9.b gs?	B7. FIRM Panel Effective/ Revised Date 09-29-2006 (BFE) data or base mined Other/S	n 1.0 foot above adjaces of in E MAP (FIRM) INFO ty Name bunty B8. Flood Zone(s) AE flood depth entered ource:	ORMATION B9. Base Flood El (Zone AO, use 6' in Item B9:	New Jersey evation(s) Base Flood Depth)

11-2-2021

OMB No. 1660-0008 **ELEVATION CERTIFICATE** Expiration Date: November 30, 2018 IMPORTANT: In these spaces, copy the corresponding information from Section A. FOR INSURANCE COMPANY USE Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. Policy Number: 23 Sands Point Road City ZIP Code State Company NAIC Number Waretown **New Jersey** 08758 SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED) ☐ Construction Drawings* C1. Building elevations are based on: ☐ Building Under Construction* X Finished Construction *A new Elevation Certificate will be required when construction of the building is complete. C2. Elevations - Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, AR/AO. Complete Items C2.a-h below according to the building diagram specified in Item A7. In Puerto Rico only, enter meters. Benchmark Utilized: 4.27' (Leica SmartNet) Vertical Datum: NAVD88 Indicate elevation datum used for the elevations in items a) through h) below. ☐ NGVD 1929
☐ NAVD 1988
☐ Other/Source: Datum used for building elevations must be the same as that used for the BFE. Check the measurement used. 5.20 a) Top of bottom floor (including basement, crawlspace, or enclosure floor) X feet meters 14.30 ★ feet ☐ meters b) Top of the next higher floor N/A c) Bottom of the lowest horizontal structural member (V Zones only) ☐ feet ☐ meters 4.90 |X| feet d) Attached garage (top of slab) meters e) Lowest elevation of machinery or equipment servicing the building N/A ☐ feet meters (Describe type of equipment and location in Comments) 4.60 x feet f) Lowest adjacent (finished) grade next to building (LAG) meters 4.70 g) Highest adjacent (finished) grade next to building (HAG) meters h) Lowest adjacent grade at lowest elevation of deck or stairs, including 4.90 |X | feet meters structural support SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION This certification is to be signed and sealed by a land surveyor, engineer, or architect authorized by law to certify elevation information. I certify that the information on this Certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. Were latitude and longitude in Section A provided by a licensed land surveyor?

Yes
No Check here if attachments. Certifier's Name License Number Marc J. Cifone 24GS04132900 Title President Place Company Name Seal Lakeland Surveying, Inc. **Address** Here 4 West Main Street City State ZIP Code Rockaway 07866 **New Jersey** Signature Date Telephone Ext. 07-14-2020 (973) 625-5670 Copy all pages of this Elegather Certificate and all attachments for (1) community official, (2) insurance agent/company, and (3) building owner, Comments (including type of equipment and location, per C2(e), if applicable) Ocean County, NJ - Preliminally IFIRM Map No. 34029C0416G revised January 30, 2015 - Zone AE / BFE 8 (NAVD88)



ELEVATION CERTIFICATE

OMB No. 1660-0008 Expiration Date: November 30, 2018

IMP	ORTANT: In these spaces, copy the correspon	ding information fror	n Section A.	FOR INSURANCE COMPANY USE
	lding Street Address (including Apt., Unit, Suite, ar Sands Point Road	nd/or Bldg. No.) or P.O	. Route and Box No.	Policy Number:
City Wa	retown	State New Jersey	ZIP Code 08758	Company NAIC Number
	SECTION E – BUILDING E FOR ZON	LEVATION INFORM NE AO AND ZONE A	ATION (SURVEY NOT (WITHOUT BFE)	REQUIRED)
con	Zones AO and A (without BFE), complete Items Enplete Sections A, B,and C. For Items E1–E4, use er meters.	E1–E5. If the Certificate natural grade, if availa	is intended to support a ble. Check the measure	LOMA or LOMR-F request, ment used. In Puerto Rico only,
E1.	Provide elevation information for the following an the highest adjacent grade (HAG) and the lowest a) Top of bottom floor (including basement,			r the elevation is above or below
	crawlspace, or enclosure) is b) Top of bottom floor (including basement,		feet meter	
E2.	crawlspace, or enclosure) is For Building Diagrams 6–9 with permanent flood	openings provided in S		
	the next higher floor (elevation C2.b in the diagrams) of the building is		feet meter	
	Attached garage (top of slab) is		feet	rs above or below the HAG.
	Top of platform of machinery and/or equipment servicing the building is		feet meter	
E5.	Zone AO only: If no flood depth number is availal floodplain management ordinance? Yes [ble, is the top of the bo Dunknown.	ttom floor elevated in ac The local official must of	cordance with the community's certify this information in Section G.
	SECTION F - PROPERTY OV	VNER (OR OWNER'S	REPRESENTATIVE) CE	RTIFICATION
The com	property owner or owner's authorized representation property owner or owner's authorized representation property.	tive who completes Se The statements in Sec	ctions A, B, and E for Zo tions A, B, and E are cor	ne A (without a FEMA-issued or rect to the best of my knowledge.
Pro	perty Owner or Owner's Authorized Representative	e's Name		
Add	Iress	City	Sta	ate ZIP Code
Sigi	nature	Date	Те	lephone
Con	nments			
				☐ Check here if attachments.

ELEVATION CERTIFICATE

OMB No. 1660-0008 Expiration Date: November 30, 2018 FOR INCURANCE COMPANY LICE

IMPORTANT: In these spaces, copy the corr	responding information	n from Section A.	FOR INSURANCE COMPANY USE
Building Street Address (including Apt., Unit, S 23 Sands Point Road	suite, and/or Bldg. No.) o	r P.O. Route and Box	No. Policy Number:
City Waretown	State New Jersey	ZIP Code 08758	Company NAIC Number
SECTION	ON G - COMMUNITY IN	FORMATION (OPTIO	ONAL)
The local official who is authorized by law or o Sections A, B, C (or E), and G of this Elevation used in Items G8–G10. In Puerto Rico only, er	n Certificate. Complete t	ne community's floodp he applicable item(s) a	lain management ordinance can complete and sign below. Check the measurement
			igned and sealed by a licensed surveyor, licate the source and date of the elevation
G2. A community official completed Sect or Zone AO.	tion E for a building loca	ted in Zone A (without	a FEMA-issued or community-issued BFE)
G3. The following information (Items G4-	-G10) is provided for co	mmunity floodplain ma	anagement purposes.
G4. Permit Number	G5. Date Permit Issue	ed	G6. Date Certificate of Compliance/Occupancy Issued
G7. This permit has been issued for:	New Construction	Substantial Improvem	nent
G8. Elevation of as-built lowest floor (includin of the building:	g basement)		feet meters Datum
G9. BFE or (in Zone AO) depth of flooding at	the building site:		feet meters Datum
G10. Community's design flood elevation:			feet meters Datum
Local Official's Name		Title	
Community Name		Telephone	
Signature		Date	
Comments (including type of equipment and lo	cation, per C2(e), if appl	icable)	
			Check here if attachments.

BUILDING PHOTOGRAPHS

ELEVATION CERTIFICATE

See Instructions for Item A6.

OMB No. 1660-0008 Expiration Date: November 30, 2018

IMPORTANT: In these spaces, o	FOR INSURANCE COMPANY USE		
Building Street Address (including 23 Sands Point Road	Policy Number:		
City	State	ZIP Code	Company NAIC Number
Waretown	New Jersey	08758	

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least 2 building photographs below according to the instructions for Item A6. Identify all photographs with date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8. If submitting more photographs than will fit on this page, use the Continuation Page.



Photo One

Photo One Caption FRONT LEFT - July 13, 2020 Clear Photo One



Photo Two

Photo Two Caption REAR LEFT - July 13, 2020

Clear Photo Two

BUILDING PHOTOGRAPHS

ELEVATION CERTIFICATE

Continuation Page

OMB No. 1660-0008 Expiration Date: November 30, 2018

IMPORTANT: In these spaces,	FOR INSURANCE COMPANY USE Policy Number:		
Building Street Address (including 23 Sands Point Road			
City	State	ZIP Code	Company NAIC Number
Waretown	New Jersey	08758	

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.




Photo Three Caption FRONT RIGHT - July 13, 2020

Clear Photo Three




Photo Four Caption REAR RIGHT - July 13, 2020

Clear Photo Four




V ZONE DESIGN CERTIFICATE

Name Gary Belfer	V 20112 D21	Policy Number (Insu	ırance Co. l	Jse)		
Building Address or Other Descript	ion 23 Sands					
	ty Ocean	State	NJ Zip	Code	08758	
SE	CTION I: Flood Insura	nnce Rate Map (FIRN	l) Informati	on		
Community No. 340518	Panel No. 0416 Suf	fix G FIRM Date	1/30/15	FIRM	Zone(s) Coas	tal A
[NOTE: This section docume	SECTION II: Elevatio ents elevations used in			e for an l	Elevation Certific	cate.]
 Elevation of the Bottom of Lower Base Flood Elevation (BFE) Elevation of Lowest Adjacent Grades Approximate Depth of Anticipate Embedment Depth of Pilings or Francisco 	adeed Scour/Erosion used f	or Foundation Design	· · · · · · · · · · · · · · · · · · ·	4.8 fee 4.0 fe	et (NAVD88) et (NAVD88) et (NAVD88)	
[NOTE, T	SECTION III: Zone I his section must be cer			architec	t.]	
I certify that: (1) I have developed design and methods of constructifollowing provisions:	on to be used are in	accordance with acc	epted stan	dards of	f practice for me	eeting the
 The bottom of the lowest to or above the BFE; and 	norizontal structural me	mber of the lowest flo	oor (excludi	ng piles	and columns) is	elevated
The pile and column found movement due to the effect loading values used are the applicable State or local bus conditions associated with	cts of the wind and wa nose associated with th uilding code. The poten	ter loads acting simu e base flood. Wind lo tial for scour and eros	Itaneously on the court of the	on all bu es used	ilding componer are those require	nts. Wate red by the
	TION IV: Breakaway V	_				
	s section must also be c alls exceed a design sa					
I certify that (1) I have developed of design and methods of construction practice for meeting the following performance of the Breakaway wall collapses of the elevated portion of the or other structural damage components (wind and ward).	on to be used for the provisions: hall result from a water building and supporting due to the effects	load less than that what g foundation system so f wind and water	e in accord nich would o shall not be loads actin	ance wi occur du subject	th accepted sta ring the base flo- to collapse, disp	ndards o od; and blacement
	SECTIONIV:	Certification and Se	al *Site is l	ocated	within a Coasta	al A Zon
This certification is to be signed an structural designs. I certify the Certification Statement in Section I	Design Certification	d professional engine n Statement in Section				
Matthew C Hockenbury		49637				\neg
Certifier's Name President	MCH Engineering	icense Number			Place Seal	
	ompany Name Toms River	NJ	08755		Here	
Address	City 9~17~20	State 732-569-35	ZIP 92			

Telephone

Date

Signature





ICC-ES | (800) 423-6587 | (562) 699-0543 | www.icc-es.org

ESR-2074

Reissued 02/2017 This report is subject to renewal 02/2019.

DIVISION: 08 00 00—OPENINGS

SECTION: 08 95 43—VENTS/FOUNDATION FLOOD VENTS

REPORT HOLDER:

SMARTVENT PRODUCTS, INC.

430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: MODELS #1540-520; #1540-521; #1540-510; #1540-511; #1540-570; #1540-574; #1540-524; #1540-514



Look for the trusted marks of Conformity!

"2014 Recipient of Prestigious Western States Seismic Policy Council (WSSPC) Award in Excellence"







ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.



ESR-2074

Reissued February 2017 Revised November 2017 This report is subject to renewal February 2019.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43—Vents/Foundation Flood Vents

REPORT HOLDER:

SMARTVENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368 www.smartvent.com info@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: MODELS #1540-520; #1540-521; #1540-510; #1540-511; #1540-570; #1540-574; #1540-524; #1540-514

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2015, 2012, 2009 and 2006 International Building Code[®] (IBC)
- 2015, 2012, 2009 and 2006 International Residential Code® (IRC)
- 2013 Abu Dhabi International Building Code (ADIBC)[†]

[†]The ADIBC is based on the 2009 IBC. 2009 IBC code sections referenced in this report are the same sections in the ADIBC.

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent[®] units are engineered mechanically operated flood vents (FVs) employed to equalize hydrostatic pressure on walls of enclosures subject to rising or falling flood waters. Certain models also allow natural ventilation.

3.0 DESCRIPTION

3.1 General:

When subjected to rising water, the Smart Vent[®] FVs internal floats are activated, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The FV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water,

the buoyant release device causes the unit to unlatch, allowing the door to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel. Smart Vent Automatic Foundation Flood Vents are available in various models and sizes as described in Table 1. The SmartVENT Stacking Model #1540-511 and FloodVENT Stacking Model #1540-521 units each contain two vertically arranged openings per unit.

3.2 Engineered Opening:

The FVs comply with the design principle noted in Section 2.7.2.2 and Section 2.7.3 of ASCE/SEI 24-14 [Section 2.6.2.2 of ASCE/SEI 24-05 (2012, 2009, 2006 IBC and IRC)] for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent FVs must be installed in accordance with Section 4.0.

3.3 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with \$^1_{4}\$-inch-by-\$^1_{4}\$-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT® Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other FVs recognized in this report do not offer natural ventilation.

4.0 DESIGN AND INSTALLATION

SmartVENT® and FloodVENT® are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. Installation clips allow mounting in masonry and concrete walls of any thickness. In order to comply with the engineered opening design principle noted in Section 2.7.2.2 and 2.7.3 of ASCE/SEI 24-14 [Section 2.6.2.2 of ASCE/SEI 24-05 (2012, 2009, 2006 IBC and IRC)], the Smart Vent® FVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area.
- With a minimum of one FV for every 200 square feet (18.6 m²) of enclosed area, except that the SmartVENT® Stacking Model #1540-511 and FloodVENT® Stacking Model #1540-521 must be

installed with a minimum of one FV for every 400 square feet (37.2 m²) of enclosed area.

- Below the base flood elevation.
- With the bottom of the FV located a maximum of 12 inches (305.4 mm) above the higher of the final grade or floor and finished exterior grade immediately under each opening.

5.0 CONDITIONS OF USE

The Smart Vent[®] FVs described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

5.1 The Smart Vent[®] FVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.

5.2 The Smart Vent® FVs must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Mechanically Operated Flood Vents (AC364), dated August 2015.

7.0 IDENTIFICATION

The Smart VENT® models recognized in this report must be identified by a label bearing the manufacturer's name (Smartvent Products, Inc.), the model number, and the evaluation report number (ESR-2074).

TABLE 1-MODEL SIZES

MODEL NAME	MODEL NUMBER	MODEL SIZE (in.)	COVERAGE (sq. ft.)
FloodVENT [®]	1540-520	15 ³ / ₄ " X 7 ³ / ₄ "	200
SmartVENT [®]	1540-510	15 ³ / ₄ " X 7 ³ / ₄ "	200
FloodVENT [©] Overhead Door	1540-524	15 ³ / ₄ " X 7 ³ / ₄ "	200
SmartVENT [®] Overhead Door	1540-514	15 ³ / ₄ " X 7 ³ / ₄ "	200
Wood Wall FloodVENT [®]	1540-570	14" X 8 ³ / ₄ "	200
Wood Wall FloodVENT® Overhead Door	1540-574	14" X 8 ³ / ₄ "	200
SmartVENT [®] Stacker	1540-511	16" X 16"	400
FloodVent [®] Stacker	1540-521	16" X 16"	400

For SI: 1 inch = 25.4 mm; 1 square foot = m^2




FIGURE 1-SMART VENT: MODEL 1540-510




FIGURE 2—SMART VENT MODEL 1540-520




FIGURE 3—SMART VENT: SHOWN WITH FLOOD DOOR PIVOTED OPEN



ESR-2074 CBC and CRC Supplement

Issued February 2017 Revised November 2017 This report is subject to renewal February 2019.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43—Vents/Foundation Flood Vents

REPORT HOLDER:

SMARTVENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368 www.smartvent.com info@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: MODELS #1540-520; #1540-521; #1540-510; #1540-511; #1540-570; #1540-574; #1540-524; #1540-514

1.0 REPORT PURPOSE AND SCOPE

Purpose:

The purpose of this evaluation report supplement is to indicate that Smart Vent[®] Automatic Foundation Flood Vents, recognized in ICC-ES master evaluation report ESR-2074, have also been evaluated for compliance with codes noted below.

Applicable code edition:

- 2016 California Building Code (CBC)
- 2016 California Residential Code (CRC)

2.0 CONCLUSIONS

2.1 CBC:

The Smart Vent® Automatic Foundation Flood Vents, described in Sections 2.0 through 7.0 of the master evaluation report ESR-2074, comply with 2016 CBC Chapter 12, provided the design and installation are in accordance with the 2015 International Building Code® (IBC) provisions noted in the master report and the additional requirements of CBC Chapters 12, 16 and 16A, as applicable.

The products recognized in this supplement have not been evaluated under CBC Chapter 7A for use in the exterior design and construction of new buildings located in any Fire Hazard Severity Zone within State Responsibility Areas or any Wildland-Urban Interface Fire Area.

2.2 CRC:

The Smart Vent® Automatic Foundation Flood Vents, described in Sections 2.0 through 7.0 of the master evaluation report ESR-2074, comply with the 2016 CRC, provided the design and installation are in accordance with the 2015 *International Residential Code*® (IRC) provisions noted in the master report.

The products recognized in this supplement have not been evaluated under 2016 CRC Chapter R337, for use in the exterior design and construction of new buildings located in any Fire Hazard Severity Zone within State Responsibility Areas or any Wildland-Urban Interface Fire Area.

The products recognized in this supplement have not been evaluated for compliance with the International Wildland–Urban Interface $Code^{\mathfrak{S}}$.

This supplement expires concurrently with the master report, reissued February 2017 and revised November 2017.



ESR-2074 FBC Supplement

Reissued February 2017 Revised November 2017 This report is subject to renewal February 2019.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS

Section: 08 95 43-Vents/Foundation Flood Vents

REPORT HOLDER:

SMARTVENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368 www.smartvent.com info@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: MODELS #1540-520; #1540-521; #1540-510; #1540-511; #1540-570; #1540-574; #1540-524; #1540-514

1.0 REPORT PURPOSE AND SCOPE

Purpose:

The purpose of this evaluation report supplement is to indicate that Smart Vent® Automatic Foundation Flood Vents, recognized in ICC-ES master report ESR-2074, have also been evaluated for compliance with the codes noted below.

Applicable code editions:

- 2017 Florida Building Code—Building
- 2017 Florida Building Code—Residential

2.0 CONCLUSIONS

The Smart Vent® Automatic Foundation Flood Vents, described in Sections 2.0 through 7.0 of the master evaluation report ESR-2074, comply with the Florida Building Code-Building and the FRC, provided the design and installation are in accordance with the 2015 International Building Code® provisions noted in the master report.

Use of the Smart Vent® Automatic Foundation Flood Vents has also been found to be in compliance with the High-Velocity Hurricane Zone provisions of the Florida Building Code—Building and the Florida Building Code—Residential.

For products falling under Florida Rule 9N-3, verification that the report holder's quality assurance program is audited by a quality assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the master report, reissued February 2017 and revised November 2017.

